


NOTES:

- MATERIAL:
- FR-4. THICKNESS 0.062 COPPER 4 OZ - ALL LYRS
- LAYERS 4
- FINISH:
- ☐ Immersion Gold
  - ☐ Edge connector fingers shall be plated with Nickel/Gold, ≥ 20 microinches gold.
  - ☐ FLASH Gold
  - ☐ Immersion Tin
  - ☒ Solder Mask Over Bare Copper with Hot Air Solder Level
  - ☐ ENIG



Drill Table				
Hole Dia (inch)	Symbol	Quantity	Plated	
0.010	+	71	Yes	
0.018	X	17	Yes	
0.025	Y	242	Yes	
0.035	-	4	Yes	
0.038	Σ	27	Yes	
0.039	M	12	Yes	
0.042	□	24	Yes	
0.047	⊞	8	Yes	
0.047	◇	4	No	
0.051	◇	2	Yes	
0.059	⊞	12	Yes	
0.063	◇	14	Yes	
0.065	⊞	32	Yes	
0.075	◇	6	Yes	
0.079	⊞	4	Yes	
0.098	◇	4	Yes	
0.125	⊞	2	No	
0.150	◇	7	No	
0.197	○	4	Yes	

SOLDERMASK - DYNACHEM EPIC 200 LPI OR EQUIVALENT.

COLOR-GREEN

SILKSCREEN - WHITE

USE ARTWORK SET NO. 04-07149 REV 0.2

ANY ALTERNATIVES TO THE ABOVE SPECIFICATIONS MUST BE APPROVED BY THE ENGINEERING DEPARTMENT AT MICROCHIP.

THIS PCB TO BE MANUFACTURED TO MEET ALL ACCEPTANCE LEVELS OF A CLASS 2 PCB PER ANSI/IPC-A-600F.